

Pipe Inch		Max. Working Pressure psi/ kPa	90°Elbow - No.105S			45°Elbow - No.106S			Equal Tee - No.107S			End cap - No.155S		
Nominal Size	Actual Size in. / mm		Part Number	C to E in. / mm	Approx. Wgt. Ea. lb. / kg	Part Number	C to E in. / mm	Approx. Wgt. Ea. lb. / kg	Part Number	C to E in. / mm	Approx. Wgt. Ea. lb. / kg	Part Number	E to E in. / mm	Approx. Wgt. Ea. lb. / kg
1-1/4"	1.660 42.2	300 2070	105S125	2.25 57.2	0.9 0.4	106S125	1.75 44.5	0.6 0.3	107S125	2.25 57.2	1.2 0.5	155S125	1.00 25.4	0.5 0.2
1-1/2"	1.900 48.3	300 2070	105S150	2.50 63.5	1.3 0.6	106S150	1.75 44.5	1.1 0.5	107S150	2.50 63.5	1.8 0.8	155S150	1.00 25.4	0.6 0.3
2"	2.375 60.3	300 2070	105S200	2.75 69.8	1.5 0.7	106S200	2.00 50.8	1.3 0.6	107S200	2.75 69.8	2.2 1.0	155S200	1.00 25.4	0.7 0.3
2 1/2"	2.875 73.0	300 2070	105S250	3.00 76.2	2.2 1.0	106S250	2.25 57.2	2.0 0.9	107S250	3.00 76.2	3.1 1.4	155S250	1.00 25.4	0.8 0.4
3"	3.500 88.9	300 2070	105S300	3.38 85.9	3.1 1.4	106S300	2.50 63.5	2.6 1.2	107S300	3.38 85.9	4.8 2.2	155S300	1.00 25.4	1.3 0.6
4"	4.500 114.3	300 2070	105S400	4.00 101.6	5.9 2.7	106S400	3.00 76.2	4.6 2.1	107S400	4.00 101.6	7.7 3.5	155S400	1.06 27.0	2.0 0.9
5"	5.563 141.3	300 2070	105S500	4.88 124.0	8.0 3.6	106S500	3.25 82.6	7.5 3.4	107S500	4.88 124.0	10.5 4.8	155S500	1.06 27.0	3.5 1.6
6"	6.625 168.3	300 2070	105S600	5.50 139.7	14.9 6.6	106S600	3.50 88.9	10.8 4.9	107S600	5.50 139.7	24.2 11.0	155S600	1.06 27.0	4.8 2.2
8"	8.625 219.1	300 2070	105S800	6.81 173.0	26.5 12.0	106S800	4.25 107.9	18.9 8.6	107S800	6.95 176.5	38.4 17.4	155S800	1.20 30.1	9.3 4.2